



**SITCO ANTENNAS**

PORTLAND, OREGON USA

**LOW-NOISE PREAMPLIFIER**  
**PA24-X-xx SINGLE CHANNEL TUNED**

10330 N.E. Marx St,  
P.O. Box 20456,  
Portland, OR 97220

Ph: (503) 253-2000  
Fax: (503) 253-2009  
E-mail: [sitco@simplicitytool.com](mailto:sitco@simplicitytool.com)  
Website: [www.simplicitytool.com](http://www.simplicitytool.com)

Rev. 02-A



# SITCO ANTENNAS

PORTLAND, OREGON USA

Sitco / Triax PA24-series preamplifiers are designed for critical professional applications requiring high gain, very low noise figures, high output level, narrow bandwidth with flat response, tight RF shielding and rugged mechanical design for high reliability. The preamps are housed in heavy weatherproof die-cast aluminum housings equipped with hardware for mast mounting. F connectors and 75-ohm impedance are standard while N connectors and/or 50-ohm impedance are available.

These preamps require 24 VOLT DC power (negative ground) which is usually supplied via the output coaxial cable. As an option, DC may be fed directly into a third cable port in the preamp housing. DC power may be supplied by the Sitco PS24 power supply or from any other suitable source.

## PA24 SERIES PREAMPLIFIER

